



Filament Lamps

americanlite®

We light your world™





americanlite.







G80/95/125



Filament Dimmable

















• IP20 Damp Location

- Clear and Amber
- Working temperature at -20°C~45°C
- Recommended use: No more than 15 hours / day to avoid product damage or voided warranty
- Indoor Use

Model	Item	W	Base	Lumens	Diameter	Length	Glass	CCT (Clear)	
C35T C35T C35T	AL800D AL801D AL802D	4W 4W 4W	E12 E14 E27	480lm 480lm 480lm	35mm 35mm 35mm	97mm 97mm 93mm	C Clear	2 2700K 3 3000K 4 4000K 6 6500K	
C35F C35F C35F	AL803D AL804D AL805D	4W 4W 4W	E12 E14 E27	480lm 480lm 480lm	35mm 35mm 35mm	117mm 117mm 113mm	Glass A Amber	CCT (Amber) 1 2300K	
A60 A60	AL806D AL807D	4W 6W	E27 E27	480lm 720lm	60mm 60mm	105mm 105mm		2 2700K	
ST64	AL808D	4W	E27	480lm	64mm	144mm			
G45 G45 G45 G45 G45 G45	AL809D AL810D AL811D AL812D AL813D AL814D	2W 2W 2W 4W 4W	E12 E14 E27 E12 E14 E27	240lm 240lm 240lm 480lm 480lm 480lm	45mm 45mm 45mm 45mm 45mm	78mm 78mm 72mm 78mm 78mm 72mm			
G80	AL815D	4W	E27	480lm	80mm	120mm			
G95	AL816D	4W	E27	480lm	95mm	136mm			
G125	AL817D	4W	E27	480lm	125mm	176mm			
Notes									

Notes

- Lumen tolerance = ± 10%
- Lumen tolerance Amber = 20% less than clear
- PF: C35 and G45 = > 0.40

• With waterproof fixtures, suitable for outdoors

Packing information __

For Color Box

Model	CBM (master)	Pieces per master	Master box(cm)
C35T	0.0183	100	39 x 20.5 x 23
C35F	0.0219	100	39 x 20.5 x 27.5
A60	0.0690	100	71.5 x 35 x 27.6
ST64	0.0579	100	79 x 39 x 18.8
G45	0.0249	100	49 x 25.5 x 20
G80	0.0548	100	43.5 x 43.5 x 29
G95	0.3419	50	51.5 x 41.5 x 16
G125	0.0734	50	66 x 53 x 21

americanlite.



americanlite.









Filament

















- IP20 Damp Location
- Clear and Amber
- Working temperature at -20°C~45°C
- Recommended use: No more than 15 hours / day to avoid product damage or voided warranty
- Indoor Use

Model	Item	W	Base	Lumens	Diameter	Length	Glass	CCT (Clear)
C35T C35T C35T	AL800X AL801X AL802X	4W 4W 4W	E12 E14 E27	480lm 480lm 480lm	35mm 35mm 35mm	97mm 97mm 93mm	C Clear	2 2700K 3 3000K 4 4000K 6 6500K
C35F C35F C35F	AL803X AL804X AL805X	4W 4W 4W	E12 E14 E27	480lm 480lm 480lm	35mm 35mm 35mm	117mm 117mm 113mm	Glass A Amber	CCT (Amber) 1 2300K
A60 A60	AL806X AL807X	4W 6W	E27 E27	480lm 720lm	60mm 60mm	105mm 105mm		2 2700K
ST64	AL808X	4W	E27	480lm	64mm	144mm		
G45 G45 G45 G45 G45 G45	AL809X AL810X AL811X AL812X AL813X AL814X	2W 2W 2W 4W 4W	E12 E14 E27 E12 E14 E27	240m 240lm 240lm 480lm 480lm 480lm	45mm 45mm 45mm 45mm 45mm	78mm 78mm 72mm 78mm 78mm 72mm		
G80	AL815X	4W	E27	480lm	80mm	120mm		
G95	AL816X	4W	E27	480lm	95mm	136mm		
G125	AL817X	4W	E27	380lm	125mm	176mm		

Notes

- Lumen tolerance = ± 10%
- Lumen tolerance Amber = 20% less than clear
- PF: C35 and G45 = > 0.40

Packing information __

For Color Box

Model	CBM (master)	Pieces per master	Master box(cm)
C35T	0.0183	100	39 x 20.5 x 23
C35F	0.0219	100	39 x 20.5 x 27.5
A60	0.0549	100	64 x 33 x 26
ST64	0.0761	100	68 x 35 x 32
G45	0.0249	100	49 x 25.5 x 20
G80	0.0548	100	43.5 x 43.5 x 29
G95	0.3419	50	51.5 x 41.5 x 16
G125	0.0734	50	66 x 53 x 21

• With waterproof fixtures, suitable for outdoors

americanlite.

americanlite.





Warranty

Americanlite_® is pleased to provide a 5 year limited warranty covering the LED Lamps in this catalogue. Americanlite_® warrants that the LED Lamps comply with Americanlite_®'s published specifications and are free from defects in materials and workmanship.

All our equipment is CE, ETL or UL approved and manufactured with approved components. Americanlite_® reserves the right to change or improve the design or components of any of its products due to parts availability or changes in standards, without assuming any obligation to modify any product previously manufactured and without notice. All equipment is tested and inspected before shipment.

This warranty is void if the product is operated outside of its normal operating conditions. The foregoing warranty does not apply to failures caused by acts of God or as a result of any abuse, misuse, abnormal use, or use in violation of any applicable standard, code or instructions for use in installations, including, but not limited to, those contained in the Standards for the International Electrotechnical Commission. Americanlite® reserves and has the right to examine failed lamp to determine the cause of failure, excessive lumen depreciation and patterns of usage.

americanlite. 4