



# UL Vinyl Electrical Tape

americanlite®



We light your world™





## Pro 33™ Series

### UL Vinyl Electrical Tape Professional Grade



The demand for dependable electrical insulation is continuously rising as power usage rises in contemporary residences, workplaces, and manufacturing facilities.

Electrical insulation tape, commonly known as PVC electrical tape, insulates a wide range of industrial processes and parts, including motors, transformers, capacitors, and voltage regulators, and safeguards people and property from electrical shorts and leakage.

In order to meet the insulation and identification requirements of indoor and outdoor wire and cable connections the tapes have high flame retardant, strong resistance to UV light, humidity, acids and alkalis, corrosion, and harsh weather conditions. They are also lead-free and environmentally benign. The tapes may be securely wrapped for extended periods of time without edge curl, flagging, lifting, or adhesive foaming because to their mechanical strength and conformability.

Three key client groups are targeted by the design of Americanlite® electrical insulation tapes: professional, commercial, and general-purpose. They come in a variety of sizes and thicknesses to meet different compliance standards.

#### Ordering information

Model	Size (Imperial)	Size (Metric)	Thickness w/o liner (Imperial)	Thickness w/o liner (Metric)
AL900002	0.75 in x 60 ft	19.05mm x 18.288m	0.007 in	0.18mm

#### Notes

- Adhesive Type: Rubber
- Backing (Carrier) Material: PVC
- Voltage Rating: 600V
- Dielectric Strength: 40 kV/mm
- Elongation at Break: 200% avg
- Max. Operating Temp.: 90°C / 194°F
- Min. Operating Temp.: 0°C / 32°F

#### STORAGE AND SHELF LIFE

The shelf life of the product is five years when stored at 20-30°C, max 65% relative humidity and out of direct sunlight, in original packaging.



#### Packing information

Model	PCS per Carton	Master Box Dimensions (cm)	CBM (Master)	G.W.
AL900002	100	49 x 40 x 13.5	0.0264	11



## 900 Proflex™ Series

### UL Vinyl Electrical Tape General Use



The demand for dependable electrical insulation is continuously rising as power usage rises in contemporary residences, workplaces, and manufacturing facilities.

Electrical insulation tape, commonly known as PVC electrical tape, insulates a wide range of industrial processes and parts, including motors, transformers, capacitors, and voltage regulators, and safeguards people and property from electrical shorts and leakage.

In order to meet the insulation and identification requirements of indoor and outdoor wire and cable connections the tapes have high flame retardant, strong resistance to UV light, humidity, acids and alkalis, corrosion, and harsh weather conditions. They are also lead-free and environmentally benign. The tapes may be securely wrapped for extended periods of time without edge curl, flagging, lifting, or adhesive foaming because to their mechanical strength and conformability.

Three key client groups are targeted by the design of Americanlite® electrical insulation tapes: professional, commercial, and general-purpose. They come in a variety of sizes and thicknesses to meet different compliance standards.

### Ordering information

Model	Size (Imperial)	Size (Metric)	Thickness w/o liner (Imperial)	Thickness w/o liner (Metric)	Color Options
AL900000	0.75 in x 60 ft	19.05mm x 18.288m	0.007 in	0.18mm	B Black W White R Red G Green Y Yellow
AL900001	0.75 in x 30 ft	19.05mm x 9.144m	0.007 in	0.18mm	

### Notes

- Adhesive Type: Rubber
- Backing (Carrier) Material: PVC
- Voltage Rating: 600V
- Dielectric Strength: 40 kV/mm
- Elongation at Break: 200% avg
- Max. Operating Temp.: 90°C / 194°F
- Min. Operating Temp.: 0°C / 32°F

### STORAGE AND SHELF LIFE

The shelf life of the product is five years when stored at 20-30°C, max 65% relative humidity and out of direct sunlight, in original packaging.

### Packing information

Model	PCS per Carton	Master Box Dimensions (cm)	CBM (Master)	G.W.
AL900000	100	40.5 x 17.2 x 21	0.0146	9.93
AL900001	100	33.5 x 14.2 x 21	0.0099	8.93



## Warranty

Americanlite® is pleased to provide a 5 year limited warranty covering the Electrical Tapes in this catalogue. Americanlite® warrants that the Tapes to comply with Americanlite®'s published specifications and are free from defects in materials and workmanship.

All our equipment is CE, ETL or UL approved and manufactured with approved components. Americanlite® reserves the right to change or improve the design or components of any of its products due to parts availability or changes in standards, without assuming any obligation to modify any product previously manufactured and without notice. All equipment is tested and inspected before shipment.

This warranty is void if the product is operated outside of its normal operating conditions. The foregoing warranty does not apply to failures caused by acts of God or as a result of any abuse, misuse, abnormal use, or use in violation of any applicable standard, code or instructions for use in installations, including, but not limited to, those contained in the Standards for the International Electrotechnical Commission. Americanlite® reserves and has the right to examine failed fixtures to determine the cause of failure, excessive lumen depreciation and patterns of usage.