



Filament Lamps

americanlite®

We light your world™

CE

Filament Dimmable



- IP20 Damp Location
- Clear and Amber
- Working temperature at -20°C~45°C
- Recommended use: No more than 15 hours /day to avoid product damage or voided warranty
- Indoor Use

	VOLTS* 110-130	 15,000
 360° Beam Angle*	CRI 80	PF 0.50
DIM Triac	 -20°C to 40°C	2 YEAR Warranty

Model	Item	W	Base	Lumens	Diameter	Length	Glass	CCT (Clear)	
C35T	AL800D	4W	E12	480lm	35mm	97mm	C Clear	2 2700K	
C35T	AL801D	4W	E14	480lm	35mm	97mm		3 3000K	
C35T	AL802D	4W	E27	480lm	35mm	93mm		4 4000K	
								6 6500K	
C35F	AL803D	4W	E12	480lm	35mm	117mm		Glass	CCT (Amber)
C35F	AL804D	4W	E14	480lm	35mm	117mm			
C35F	AL805D	4W	E27	480lm	35mm	113mm			
A60	AL806D	4W	E27	480lm	60mm	105mm	A Amber	1 2300K	
A60	AL807D	6W	E27	720lm	60mm	105mm		2 2700K	
ST64	AL808D	4W	E27	480lm	64mm	144mm			
G45	AL809D	2W	E12	240lm	45mm	78mm			
G45	AL810D	2W	E14	240lm	45mm	78mm			
G45	AL811D	2W	E27	240lm	45mm	72mm			
G45	AL812D	4W	E12	480lm	45mm	78mm			
G45	AL813D	4W	E14	480lm	45mm	78mm			
G45	AL814D	4W	E27	480lm	45mm	72mm			
G80	AL815D	4W	E27	480lm	80mm	120mm			
G95	AL816D	4W	E27	480lm	95mm	136mm			
G125	AL817D	4W	E27	480lm	125mm	176mm			

Notes

- Lumen tolerance = ± 10%
- Lumen tolerance Amber = 20% less than clear
- PF: C35 and G45 = > 0.40
- With waterproof fixtures, suitable for outdoors

Packing information

For Color Box

Model	CBM (master)	Pieces per master	Master box(cm)
C35T	0.0183	100	39 x 20.5 x 23
C35F	0.0219	100	39 x 20.5 x 27.5
A60	0.0690	100	71.5 x 35 x 27.6
ST64	0.0579	100	79 x 39 x 18.8
G45	0.0249	100	49 x 25.5 x 20
G80	0.0548	100	43.5 x 43.5 x 29
G95	0.3419	50	51.5 x 41.5 x 16
G125	0.0734	50	66 x 53 x 21



- IP20 Damp Location
- Clear and Amber
- Working temperature at -20°C~45°C
- Recommended use: No more than 15 hours /day to avoid product damage or voided warranty
- Indoor Use

	VOLTS* 110-130	 15,000
 360° Beam Angle*	CRI 80	PF 0.50
 -20°C to 40°C	2 YEAR Warranty	

Model	Item	W	Base	Lumens	Diameter	Length	Glass	CCT (Clear)
C35T	AL800X	4W	E12	480lm	35mm	97mm	C Clear	2 2700K
C35T	AL801X	4W	E14	480lm	35mm	97mm		3 3000K
C35T	AL802X	4W	E27	480lm	35mm	93mm		4 4000K
								6 6500K
C35F	AL803X	4W	E12	480lm	35mm	117mm	Glass	CCT (Amber)
C35F	AL804X	4W	E14	480lm	35mm	117mm		
C35F	AL805X	4W	E27	480lm	35mm	113mm		
A60	AL806X	4W	E27	480lm	60mm	105mm	A Amber	1 2300K
A60	AL807X	6W	E27	720lm	60mm	105mm		2 2700K
ST64	AL808X	4W	E27	480lm	64mm	144mm		
G45	AL809X	2W	E12	240lm	45mm	78mm		
G45	AL810X	2W	E14	240lm	45mm	78mm		
G45	AL811X	2W	E27	240lm	45mm	72mm		
G45	AL812X	4W	E12	480lm	45mm	78mm		
G45	AL813X	4W	E14	480lm	45mm	78mm		
G45	AL814X	4W	E27	480lm	45mm	72mm		
G80	AL815X	4W	E27	480lm	80mm	120mm		
G95	AL816X	4W	E27	480lm	95mm	136mm		
G125	AL817X	4W	E27	380lm	125mm	176mm		

Notes

- Lumen tolerance = ± 10%
- Lumen tolerance Amber = 20% less than clear
- PF: C35 and G45 = > 0.40
- With waterproof fixtures, suitable for outdoors

Packing information

For Color Box

Model	CBM (master)	Pieces per master	Master box(cm)
C35T	0.0183	100	39 x 20.5 x 23
C35F	0.0219	100	39 x 20.5 x 27.5
A60	0.0549	100	64 x 33 x 26
ST64	0.0761	100	68 x 35 x 32
G45	0.0249	100	49 x 25.5 x 20
G80	0.0548	100	43.5 x 43.5 x 29
G95	0.3419	50	51.5 x 41.5 x 16
G125	0.0734	50	66 x 53 x 21



Warranty

Americanlite® is pleased to provide a 2 year limited warranty covering the LED Lamps in this catalogue. Americanlite® warrants that the LED Lamps comply with Americanlite®'s published specifications and are free from defects in materials and workmanship.

All our equipment is CE, ETL or UL approved and manufactured with approved components. Americanlite® reserves the right to change or improve the design or components of any of its products due to parts availability or changes in standards, without assuming any obligation to modify any product previously manufactured and without notice. All equipment is tested and inspected before shipment.

This warranty is void if the product is operated outside of its normal operating conditions. The foregoing warranty does not apply to failures caused by acts of God or as a result of any abuse, misuse, abnormal use, or use in violation of any applicable standard, code or instructions for use in installations, including, but not limited to, those contained in the Standards for the International Electrotechnical Commission. Americanlite® reserves and has the right to examine failed lamp to determine the cause of failure, excessive lumen depreciation and patterns of usage.