




Post Top Luminaire

americanlite®

We light your world™





As urban areas are repurposed for public pedestrian scale spaces, high precision smart architectural lighting becomes more important than ever in providing beautiful visual appearances for residents, tourism and commercial activity. Lighting appropriately scaled for pedestrian scale spaces promotes comfort through security and showcases value through stunning visual appearances.


Silhouette™ Series, is inspired by nature and harnesses the energy-efficient light of LEDs. Silhouette™ Series presents a contemporary, architectural dayform providing superior illumination, designed to enhance urban spaces with beautiful visual appearances and integrated control solutions.

Silhouette™ Series utilizes premium ultra-weatherable polyester powder coatings that are specifically formulated to withstand extended outdoor exposure. Low copper content aluminum housing, provides unparalleled heat dissipation. Light distribution based on patented IK08 impact glass diffuser, creating a smooth visual, meanwhile allows a higher performance up to 143 lumens x watt. UL IP67 driver with up to 6KV Surge protection. We have added an external 10KV SPD for maximum protection.

Silhouette™ series allows you to do more, we have created one of the most versatile post top fixtures in the market. With CCT Selectable / CCT & Power Selectable options for 75-150w, and photocell fulfils the spectrum of options. Silhouette™ Series is UL and DLC certified.

Silhouette™ Series enhances the pedestrian experience to attract commercial and social activity to the “people spaces” in which we live and work. Successful “people spaces” bring the community together at night to create an environment we want to experience to the fullest.

Dimensions (mm)



Ordering information

Single CCT

Model	Power	CCT	Lumens	CCT	Options
AL577110	75w	5000K	10125	Blank	5000K
AL577111	100w	5000K	13500	4	4000K
AL577112	150w	5000K	20250	3	3000K
					3P 3-pin Photobase & Photocell 7P 7-pin Photobase & Photocell 3B 3-pin Photobase 7B 7-pin Photobase
					T3 Dist. Type III T5 Dist. Type V

2 CCT & Power Selectable

Model	Power	CCT	Lumens	Model	Power	CCT	Lumens	Model	Power	CCT	Lumens	Options
AL577116	75W			AL577117	100W			AL577118	150W			
75w	4K/5K	10500/10125		100w	4K/5K	14000/13500		150w	4K/5K	21000/20250		3P 3-pin Photobase & Photocell
60w	4K/5K	8400/8100		80w	4K/5K	11200/10800		120w	4K/5K	16800/16200		7P 7-pin Photobase & Photocell
50w	4K/5K	7000/6750		60w	4K/5K	8400/8100		100w	4K/5K	14000/13500		3B 3-pin Photobase
												7B 7-pin Photobase
												T3 Dist. Type III T5 Dist. Type V

3 CCT & Power Selectable

Model	Power	CCT	Lumens	Model	Power	CCT	Lumens	Model	Power	CCT	Lumens	Options
AL577119	75W			AL577120	100W			AL577121	150W			
75w	3K/4K/5K	9375/10725/10200		100w	3K/4K/5K	12500/14300/13600		150w	3K/4K/5K	18750/21450/20400		3P 3-pin Photobase & Photocell
60w	3K/4K/5K	7500/8580/8160		80w	3K/4K/5K	10000/11440/10880		120w	3K/4K/5K	15000/17160/16320		7P 7-pin Photobase & Photocell
50w	3K/4K/5K	6250/7150/6800		60w	3K/4K/5K	7500/8580/8160		100w	3K/4K/5K	12500/14300/13300		3B 3-pin Photobase
												7B 7-pin Photobase
												T3 Dist. Type III T5 Dist. Type V

Notes

- Lumen tolerance up to 10%
- Lumens 2 CCT 4000K = 140 lxw 5000K = 135 lxw
- Lumens 3 CCT 3000K = 125 lxw 4000K = 143 lxw 5000K = 136 lxw
- Driver: 75w = BECKY # BQE80C-130-PVF-PSA 100w = BECKY # BQE105C-130-PVF-PSA 150w = BECKY # BQE155C-130-PVF-PSA
- Surge protection: L/N-PE: 4kV, L-N: 6kV
- 10kV SPD: ZYS-P10A
- LEDs = Lumileds 2835
- 3000K not available for 150w
- EPA: 75w-150w=0.8ft²
- 100,000 hours Lifespan @ <70Tc°C
- The cable is UL certified, SJOW, Black color (Ø8±0.3MM), black/white/green wire core, wire 3×0.824MM2, 18AWG, 105°C, 300V (Standard wire is 1.2m, outside 1m)
- Paint Color: RAL 8019

Packing information

Model	Pieces per master	Box Dimensions (cm)	CBM (Master)	Gross Weight (KG)
75w / 100w / 150w	1	49 x 47 x 14.5	0.0333	5.8




Photocell optional

Lumiere™

35w / 55w / 75w / 100w / 150w

Single / CCT Selectable



As urban areas are repurposed for public pedestrian scale spaces, high precision smart architectural lighting becomes more important than ever in providing beautiful visual appearances for residents, tourism and commercial activity. Lighting appropriately scaled for pedestrian scale spaces promotes comfort through security and showcases value through stunning visual appearances.

Lumiere™ Series, is inspired by nature and harnesses the energy-efficient light of LEDs. Lumiere™ Series presents a contemporary, architectural dayform providing superior illumination, designed to enhance urban spaces with beautiful visual appearances and integrated control solutions.


Lumiere™ Series utilizes premium ultra-weatherable polyester powder coatings that are specifically formulated to withstand extended outdoor exposure. Low copper content aluminum housing, provides unparalleled heat dissipation. Light distribution based on patented IK08 impact glass diffuser, creating a smooth visual, meanwhile allows a higher performance up to 140 lumens x watt. UL IP67 driver with up to 4KV Surge protection (10KV optional).

Lumiere™ series allows you to do more, we have created one of the most versatile post top fixtures in the market. Our CCT selectable option for 35-75w, photocell and microwave sensor fulfils the spectrum of options. Lumiere™ Series is UL and DLC certified.


Lumiere™ Series enhances the pedestrian experience to attract commercial and social activity to the “people spaces” in which we live and work. Successful “people spaces” bring the community together at night to create an environment we want to experience to the fullest.

Dimensions (mm)

35w/55w/75w



100w/150w



Ordering information


Model	Power	CCT	Lumens	Beam Angle	Options	CCT
AL574169	35w	3K/4K/5K	4340/4900/4550	120°	3P 3-pin Photobase & Photocell	3 3000K (100/150w)
AL574170	55w	3K/4K/5K	6820/7700/7150	120°	7P 7-pin Photobase & Photocell	4 4000K (100/150w)
AL574171	75w	3K/4K/5K	9150/10350/9675	120°	3B 3-pin Photobase	
					7B 7-pin Photobase	
AL574172	100w	5000K	12900	90°	MS Microwave sensor	
AL574173	150w	5000K	19050	90°	S 10kV SPD	

Notes


- 1.2kV Surge protector 35w-55w
- Lumens: 100w/150w 3000K= 110lxw
100w 4000K= 125lxw / 150w =4000K 123lxw
- 75w = 120-277V
- EPA:
35w-75w = 1.5ft²
100w/150w = 1.9ft²
- The cable is UL certified, SJOW, Black color (Φ8±0.3MM), black/white/green wire core, wire 3×0.824MM², 18AWG, 105°C, 300V (Standard wire is 1.2m, outside 1m)
- Paint Color: RAL 8019

Packing information

Model	Pieces per master	Box Dimensions (cm)	CBM (Master)	Gross Weight (KG)
35w / 55w / 75w	1	73 x 51.5 x 18	0.0676	5.8
100w / 150w	1	83.5 x 58.5 x 15.5	0.0757	8.5



Lumiere™ 55w / 75w / 150w Adjustable



As urban areas are repurposed for public pedestrian scale spaces, high precision smart architectural lighting becomes more important than ever in providing beautiful visual appearances for residents, tourism and commercial activity. Lighting appropriately scaled for pedestrian scale spaces promotes comfort through security and showcases value through stunning visual appearances.


Lumiere™ Adjustable Series, is inspired by nature and harnesses the energy-efficient light of LEDs. Lumiere™ Series presents a contemporary, architectural dayform providing superior illumination, designed to enhance urban spaces with beautiful visual appearances and integrated control solutions.

We introduce a Lumiere™ Adjustable Series, to fulfill more applications, specifically those that need to put the light in certain angles or asymmetric paths. Lumiere™ Series utilizes premium ultra-weatherable polyester powder coatings that are specifically formulated to withstand extended outdoor exposure. Low copper content aluminum housing, provides unparalleled heat dissipation. Light distribution based on patented IK08 impact glass diffuser, creating a smooth visual, meanwhile allows a higher performance of 132 lumens x watt. UL IP67 driver with up to 10KV Surge protection. (10KV SPD optional).

Lumiere™ Adjustable Series allows you to do more, we have created one of the most versatile post top fixtures in the market. Fixture can be adjustable from 22° up to 90°; we also offer other options such as photocell and microwave sensor. Lumiere™ Adjustable Series is UL and DLC certified.

Lumiere™ Adjustable Series enhances the pedestrian experience to attract commercial and social activity to the “people spaces” in which we live and work. Successful “people spaces” bring the community together at night to create an environment we want to experience to the fullest.

Dimensions (mm)



Adjustable:
55w/75w: 25°, 49°, 73°, 90°
150w: 22°, 45°, 67°, 90°

Ordering information

Model	Power	CCT	Lumens	Beam Angle	Options	CCT
AL577100	55w	5000K	7425	110°	3P 3-pin Photobase & Photocell	3 3000K
AL577101	75w	5000K	10125	110°	7P 7-pin Photobase & Photocell	4 4000K
AL577102	150w	5000K	20250	90°	3B 3-pin Photobase	
					7B 7-pin Photobase	
					MS Microwave Sensor	
					S 10KV SPD	

Notes

- Lumens:
55w 3000K 128lxw / 4000K 130lxw
75w 3000K 126lxw / 4000K 128lxw
150w 3000K 130lxw / 4000K 132lxw
- 75w = 120-277V
- 55w: 1.5kV Surge protection
- 75w: L/N-PE: 4kV, L-N: 2kV
- 150w: L/N-PE: 10kV, L-N: 6kV
- EPA:
55w/75w = 1.5ft²
150w = 1.9ft²
- The cable is UL certified, SJOW, Black color (Φ8±0.3MM), black/white/green wire core, wire 3×0.824MM², 18AWG, 105°C, 300V (Standard wire is 1.2m, outside 1m)
- Paint Color: RAL 8019

Packing information

Model	Pieces per master	Box Dimensions (cm)	CBM (Master)	Gross Weight (KG)
55w / 75w	1	73 x 51.5 x 18	0.0676	5.8
150w	1	83.5 x 58.5 x 15.5	0.0757	8.5

Lunna™

30w / 50w / 70w

CCT & Power Selectable



As urban areas are repurposed for public pedestrian scale spaces, high precision smart architectural lighting becomes more important than ever in providing beautiful visual appearances for residents, tourism and commercial activity. Lighting appropriately scaled for pedestrian scale spaces promotes comfort through security and showcases value through stunning visual appearances.



Lunna™ Series, is inspired by nature and harnesses the energy-efficient light of LEDs. Lunna™ Series presents a contemporary, architectural dayform providing superior illumination, designed to enhance urban spaces with beautiful visual appearances and integrated control solutions.

Lunna™ Series utilizes premium ultra-weatherable polyester powder coatings that are specifically formulated to withstand extended outdoor exposure. Low copper content aluminum housing, provides unparalleled heat dissipation. Light distribution based on patented IK08 impact PC diffuser, creating a smooth visual, meanwhile allows a higher performance up to 150 lumens x watt. DOB Technology with 4KV Surge protection, with optional external 10KV SPD for maximum protection.

Lunna™ series allows you to do more, we have created one of the most versatile post top fixtures in the market. With CCT Selectable / CCT & Power Selectable options for 30w/50w/70w fulfils the spectrum of options.

Lunna™ Series enhances the pedestrian experience to attract commercial and social activity to the “people spaces” in which we live and work. Successful “people spaces” bring the community together at night to create an environment we want to experience to the fullest.

Dimensions (mm)



Ordering information

Item	Power	CCT	Lumens	Option
AL577108	70w	3K/4K/5K	9450/10500/10500	S1 SPD 10KV
	50w	3K/4K/5K	6750/7500/7500	
	30w	3K/4K/5K	4050/4500/4500	
AL577109	70w	22K/3K/4K	10500/9450/10500	
	50w	22K/3K/4K	7500/6750/7500	
	30w	22K/3K/4K	4500/4050/4500	

Notes

- Lumen tolerance up to 10%
- Surge protection: L/N-PE: 4kV, L-N: 4kV
- Arm Compartment: 42-60mm
- Lumens:
 - 5000K = 150 lxw
 - 4000K = 150 lxw
 - 3000K = 135 lxw
 - 2200K = 150 lxw
- LEDS = SMD 2835
- Housing wall thickness: 2mm
- Cable = 3x1.0mm²
- PC Lens thickness: 2mm
- Length = 30 cm
- Paint Color: RAL9007

Packing information

Model	Pieces per master	Box Dimensions (cm)	CBM (Master)	Gross Weight (KG)
70w/50w/30w	10	69 x 62 x 35	0.1497	21.12



Warranty

Americanlite® is pleased to provide a 5 year limited warranty covering the LED fixtures in this catalogue. Americanlite® warrants that the LED fixtures comply with Americanlite®'s published specifications and are free from defects in materials and workmanship.

All our products are UL, ETL or CE approved and manufactured with approved components. Americanlite® reserves the right to change or improve the design or components of any of its products due to parts availability or changes in standards, without assuming any obligation to modify any product previously manufactured and without notice. All equipment is tested and inspected before shipment.

This warranty is void if the product is operated outside of its normal operating conditions. The foregoing warranty does not apply to failures caused by acts of God or as a result of any abuse, misuse, abnormal use, or use in violation of any applicable standard, code or instructions for use in installations, including, but not limited to, those contained in the Standards for the International Electrotechnical Commission. Americanlite® reserves and has the right to examine failed fixtures to determine the cause of failure, excessive lumen depreciation and patterns of usage.