



LED®

Floodlite™

americanlite®

We light your world™

CE

## FLC Pro™ Series

Power & CCT Selectable

10w/20w/30w/50w

100w/150w/200w/300w



<b>IP65</b> Waterproof	<b>IK05</b> Impact Resistant
<b>Power Selectable</b> 10w/20w/30w/50w/100w/150w/200w/300w	<b>3CCT Selectable</b> 3000K/4000K/5000K
<b>Lumens up to 120 LW</b>	<b>120° Beam Angle</b>
<b>VOLTS 100-277</b>	<b>2KV Surge Protection</b>
<b>PF 0.90</b>	<b>THD &lt;20%</b>
<b>SDCM &gt;6</b>	<b>CRI &gt;80</b>
<b>3 YEARS Warranty</b>	<b>30,000 Hours</b>

Americanlite® FLC Pro™ Series floodlights are premium, highly adaptable LED luminaires engineered to provide maximum flexibility for a wide range of area-lighting applications. Built on a robust platform with proven thermal and mechanical design, the FLC Pro™ Series is optimized for projects that require field adjustability, simplified specification, and reduced inventory complexity.


The FLC Pro™ Series features Americanlite® Power and CCT Selectable technology, utilizing integrated on-fixture switching to allow field adjustment of both lumen output and correlated color temperature. Each luminaire is equipped with dual onboard switches that enable selection of 3 wattage settings and 3 correlated color temperature options, allowing a single fixture to support multiple lighting requirements. Available CCT selections include 3000K, 4000K, 5000K / 3000K, 4000K, 6500K, or 4000K, 5000K, 6500K, depending on model configuration.

This field-adjustable architecture allows installers and specifiers to fine-tune light output and color temperature at the job site, reducing the need for multiple SKUs while accommodating changing application requirements. Power selection further enables optimization of energy consumption and illumination levels without fixture replacement.

The luminaire incorporates a durable die-cast aluminum housing with an efficient heat-sink design to maintain stable thermal performance and support long-term operation across specified ambient conditions. A tempered glass lens provides enhanced impact resistance and improved safety compared to standard glass. Each fixture is also equipped with integrated 2KV surge protection, providing added resilience against electrical transients and voltage spikes commonly encountered in outdoor and commercial installations. The FLC Pro™ Series operates on a universal input voltage range of 100-277V, 50/60Hz, supporting broad installation flexibility.

Designed for wall, pole, and ground mounting, the Americanlite® FLC Pro™ Series is suitable for applications such as parking areas, security lighting, building facades, landscaping, and general area illumination. With advanced Power and CCT Selectable functionality, integrated surge protection, and a durable construction platform, the FLC Pro™ Series delivers a premium, adaptable lighting solution for projects requiring flexibility, control, and long-term performance.

### Dimensions (mm)



Model	L	W	H
10w	101.7	85.9	26
20w	131.8	107	27.3
30w	163.7	116.9	26
50w	209.8	168.2	28.6
100w	300.1	215.1	27.3
150w	334.1	255.1	29
200w	355	256	37
300w	460	310	50

### Ordering information

Item	Power	3000K	4000K	5000K	Item	Power	3000K	4000K	6500K	Item	Power	4000K	5000K	6500K	Housing
AL675140	10w	1100	1200	1200	AL675148	10w	1100	1200	1200	AL675156	10w	1200	1200	1200	<b>B</b> Black
	7w	770	840	840		7w	770	840	840		7w	840	840	840	<b>G</b> Gray
	5w	550	600	600		5w	550	600	600		5w	600	600	600	<b>W</b> White
AL675141	20w	2200	2400	2400	AL675149	20w	2200	2400	2400	AL675157	20w	2400	2400	2400	
	15w	1650	1800	1800		15w	1650	1800	1800		15w	1800	1800	1800	
	10w	1100	1200	1200		10w	1100	1200	1200		10w	1200	1200	1200	
AL675142	30w	3300	3600	3600	AL675150	30w	3300	3600	3600	AL675158	30w	3600	3600	3600	
	22w	2420	2640	2640		22w	2420	2640	2640		22w	2640	2640	2640	
	15w	1650	1800	1800		15w	1650	1800	1800		15w	1800	1800	1800	
AL675143	50w	5500	6000	6000	AL675151	50w	5500	6000	6000	AL675159	50w	6000	6000	6000	
	37w	4070	4440	4440		37w	4070	4440	4440		37w	4440	4440	4440	
	25w	2750	3000	3000		25w	2750	3000	3000		25w	3000	3000	3000	
AL675144	100w	11000	12000	12000	AL675152	100w	11000	12000	12000	AL675160	100w	12000	12000	12000	
	75w	8250	9000	9000		75w	8250	9000	9000		75w	9000	9000	9000	
	50w	5500	6000	6000		50w	5500	6000	6000		50w	6000	6000	6000	
AL675145	150w	16500	18000	18000	AL675153	150w	16500	18000	18000	AL675161	150w	18000	18000	18000	
	112w	12320	13440	13440		112w	12320	13440	13440		112w	13440	13440	13440	
	75w	8250	9000	9000		75w	8250	9000	9000		75w	9000	9000	9000	
AL675146	200w	22000	24000	24000	AL675154	200w	22000	24000	24000	AL675162	200w	24000	24000	24000	
	150w	16500	18000	18000		150w	16500	18000	18000		150w	18000	18000	18000	
	100w	11000	12000	12000		100w	11000	12000	12000		100w	12000	12000	12000	
AL675147	300w	33000	36000	36000	AL675155	300w	33000	36000	36000	AL675163	300w	36000	36000	36000	
	225w	24750	27000	27000		225w	24750	27000	27000		225w	27000	27000	27000	
	150w	16500	18000	18000		150w	16500	18000	18000		150w	18000	18000	18000	

### Notes

- Lumen & Power tolerance up to 10%
- Lumens:  
3K/4K/5K      3K/4K/55K      4K/5K/65K  
3K = 110 lwx      3K = 110 lwx      4K = 120 lwx  
4K = 120 lwx      4K = 120 lwx      5K = 120 lwx  
65K = 120 lwx      5K = 120 lwx      65K = 120 lwx
- LED Chip Brand: BMT C SMD2835
- Die cast Aluminum housing  
Thickness:  
10w -50w = 1 mm  
100w / 150w = 1.2 mm  
200w / 300w = 1.5 mm
- Tempered Glass  
Thickness:  
10w -150w = 3.2 mm  
200w / 300w = 4 mm
- Cable:  
Rubber Cable = 3\*0.75mm<sup>2</sup>  
Length: 0.21meters  
• Recommended use: 12 hours / day to prevent product damage or voided warranty

### Packing information

Model	CBM (Master)	Pieces / master	Master Carton Dim. (cm)	G.W. (KGS)
10w	0.0156	20	24 x 39.5 x 16.5	
20w	0.0225	20	30 x 39.5 x 19	
30w	0.3036	20	37.5 x 39.5 x 20.5	
50w	0.4582	20	45.5 x 39.5 x 25.5	

Model	CBM (Master)	Pieces / master	Master Carton Dim. (cm)	G.W. (KGS)
100w	0.0802	20	64.5 x 39.5 x 31.5	
150w	0.5262	10	36.5 x 39.5 x 36.5	
200w	0.0604	10	42.5 x 39.5 x 36	
300w	0.0728	5	47.5 x 46.5 x 33	

## EXC Pro™ Series

CCT Selectable  
50w/100w/150w/200w




Americanlite® LED Floodlite™ EXC Pro™ Series, a multipurpose, highly efficient, energy saving replacement for HID & halogen fixtures. With a compact and modern design, the latest SMD LED technology, offers high brightness and a high lumen maintenance factor. We have developed an outstanding combination of high performance & bright LED's to create one of the most efficient fixtures.

You have more options with Americanlite® CCT Selectable Technology to satisfy the demands of your project. We have integrated a switch to easily select the CCT of your choice.

Versatile, light and strong housing made of die-cast aluminum, featuring high heat dissipation and superior aesthetics. Corrosion resistant with longer lifetime. Tempered glass, much stronger than regular glass, reduces the risk of injury caused by jagged glass shards. Advanced heat sink design ensures LED does not exceed temperature ratings across all specified ambient conditions. Universal voltage capacity 100-277V 50/60Hz.

Ideal for indoor and outdoor area lighting such as parking, security, landscaping, facades, schools, and many more. Works well for wall mounting, pole or ground mounting.

### Dimensions (mm)



Model	L	W	H
50w	188	146	31
100w	272	217	32
150w	327	263	32
200w	378	298	34

### Ordering information

Item	Power	CCT	Lumens
AL675090	50w	3K/4K/65K	4750/6000/5000
AL675091	100w	3K/4K/65K	9500/12000/10000
AL675092	150w	3K/4K/65K	14250/18000/15000
AL675093	200w	3K/4K/65K	19000/24000/20000
AL675094	50w	3K/4K/5K	4750/6000/6000
AL675095	100w	3K/4K/5K	9500/12000/10000
AL675096	150w	3K/4K/5K	14250/18000/15000
AL675097	200w	3K/4K/5K	19000/24000/20000
AL675098	50w	4K/5K/65K	4750/6000/5000
AL675099	100w	4K/5K/65K	9500/12000/10000
AL675100	150w	4K/5K/65K	14250/18000/15000
AL675101	200w	4K/5K/65K	19000/24000/20000

Housing		Cable Length	
<b>Blank</b>	Black	<b>Blank</b>	0.15m
<b>W</b>	White	<b>C1</b>	1m



CCT Switch

### Notes

- Lumen & Power tolerance up to 10%
- Lumens:
 

3K/4K/65K	3K/4K/5K	4K/5K/65K
3K = 95 lxw	3K = 95 lxw	4K = 95 lxw
4K = 120 lxw	4K = 120 lxw	5K = 120 lxw
65K = 100 lxw	5K = 100 lxw	65K = 100 lxw
- Cable spec: = 3x0.52 mm2
- Cable length: 0.15 meters
- Glass Thickness:
 

50w / 100w = 2.2mm
150w / 200w = 3.2mm
- Recommended use: 12 hours / day to prevent product damage or voided warranty

### Packing information


Model	CBM (Master)	Pieces per master	Master Carton Dimensions (cm)	G.W. (KGS)
50w	0.0422	30	56 x 22.5 x 33.5	13.74
100w	0.0282	10	38 x 31 x 24	10.17
150w	0.0383	10	38 x 36 x 28	16.30
200w	0.0288	5	41 x 22 x 32	10.50

## FLE Max™ Series

Ultra High Efficiency Series

10w/20w/30w/50w/70w

100w/150w/200w/300w/400w



Americanlite® Max Pro™ Series floodlights are versatile, high-efficiency LED luminaires engineered to deliver reliable performance and exceptional value across a wide range of area-lighting applications. Utilizing advanced LED technology, the FLE Max™ Series achieves luminous efficacy of up to 120 lumens per watt, providing high light output with reduced energy consumption. Despite its value-focused positioning, the series is designed to meet recognized international standards, offering performance and compliance typically associated with higher-tier products.


The luminaire features a compact, modern design with a lightweight yet durable die-cast aluminum housing. The housing incorporates an advanced heat-sink architecture to ensure effective thermal management, maintaining LED junction temperatures within rated limits across specified ambient conditions. This design supports consistent light output, long operating life, and dependable performance. The corrosion-resistant construction makes the fixture suitable for both indoor and outdoor environments.

A tempered glass lens provides enhanced impact resistance compared to standard glass and improves safety by minimizing the risk of sharp fragments in the event of breakage. The FLE Max™ Series operates on a universal input voltage range of 100–277V, 50/60Hz, allowing for flexible installation across a wide range of electrical systems.


The luminaire complies with CE, RoHS, and IEC standards, demonstrating adherence to international requirements for safety, performance, and environmental responsibility. This level of certification is uncommon in economic floodlight products and reinforces the FLE Max™ Series as a dependable solution for cost-sensitive projects that still demand verified quality and compliance.

Designed for multiple mounting configurations, including wall, pole, and ground mounting, the Americanlite® FLE Max™ Series is ideal for applications such as parking areas, security lighting, building facades, landscaping, schools, and general area illumination. With strong lumen performance, robust construction, and globally recognized certifications, the FLE Max™ Series delivers long-term value for commercial and institutional lighting projects.

### Dimensions (mm)



Model	L	W	H
10w	82	67	25
20w	96	80	25
30w	128	98	25
50w	164	128	25
70w	200	152	26
100w	270	185	27
150w	330	220	27
200w	370	260	28
300w	450	330	31



Model	L	W	H
400w	393	295	37

### Ordering information

Item	Watts	Lumens	CCT	Housing	CCT	Housing
AL675130	10w	1200	6500	Black	<b>Blank</b> 6500K	<b>Blank</b> Black
AL675131	20w	2400	6500	Black	<b>5</b> 5000K	<b>W</b> White
AL675132	30w	3600	6500	Black	<b>4</b> 4000K	
AL675133	50w	6000	6500	Black	<b>3</b> 3000K	
AL675134	70w	9600	6500	Black		
AL675135	100w	12000	6500	Black		
AL675136	150w	18000	6500	Black		
AL675137	200w	24000	6500	Black		
AL675138	300w	36000	6500	Black		
AL675139	400w	48000	6500	Black		

### Notes

- Lumen & Power tolerance up to 10%
- 4K/5K/65K = 120 lxw  
3K = 110 lxw
- LED Chips: BMTC
- Cable spec: 0.2m\*0.75mm<sup>2</sup>
- Cable length: 20 cm
- Surge Protection: L-N 2KV; L, N-FG 2KV
- Tempered Glass Thickness:  
10w-30w = 3 mm  
50w-100w = 3.5 mm  
150w-400w = 4mm
- Die Cast Aluminum Housing Thickness:  
10w-20w = 0.6 mm  
30w-70w = 0.7 mm  
100w-200w = 0.8 mm  
300w = 1.3mm  
400w = 3mm
- Recommended use: 12 hours / day to prevent product damage or voided warranty

### Packing information

Model	Pieces per master	Carton Dimensions (cm)	CBM per master	Gross Weight (KG)
10w	90	33.5 x 12 x 27.5	0.0110	14.4
20w	80	40 x 32 x 25	0.0320	15.5
30w	60	35 x 32 x 31	0.0347	16.5
50w	40	39 x 32 x 29	0.0361	17.1
70w	20	45 x 32 x 18	0.0259	16.5
100w	10	34 x 31 x 21	0.0221	10.6
150w	10	37.5 x 34 x 24.5	0.0312	14.8
200w	10	41 x 35 x 28	0.0401	18.6
300w	4	50 x 16 x 36.5	0.0292	14
400w	5	42.5 x 20 x 32.5	0.0276	25



## FLE Pro™ Series

### High Efficiency Series

10w/20w/30w/50w/70w  
100w/150w/200w/300w/400w


Americanlite® FLE Pro™ Series floodlights are versatile, high-efficiency LED luminaires engineered to deliver reliable performance and exceptional value across a wide range of area-lighting applications. Utilizing advanced LED technology, the FLE Pro™ Series achieves luminous efficacy of up to 100 lumens per watt, providing high light output with reduced energy consumption. Despite its value-focused positioning, the series is designed to meet recognized international standards, offering performance and compliance typically associated with higher-tier products.

The luminaire features a compact, modern design with a lightweight yet durable die-cast aluminum housing. The housing incorporates an advanced heat-sink architecture to ensure effective thermal management, maintaining LED junction temperatures within rated limits across specified ambient conditions. This design supports consistent light output, long operating life, and dependable performance. The corrosion-resistant construction makes the fixture suitable for both indoor and outdoor environments.


A tempered glass lens provides enhanced impact resistance compared to standard glass and improves safety by minimizing the risk of sharp fragments in the event of breakage. The FLE Pro™ Series operates on a universal input voltage range of 100–277V, 50/60Hz, allowing for flexible installation across a wide range of electrical systems.

The luminaire complies with CE, RoHS, and IEC standards, demonstrating adherence to international requirements for safety, performance, and environmental responsibility. This level of certification is uncommon in economic floodlight products and reinforces the FLE Pro™ Series as a dependable solution for cost-sensitive projects that still demand verified quality and compliance.

Designed for multiple mounting configurations, including wall, pole, and ground mounting, the Americanlite® FLE Pro™ Series is ideal for applications such as parking areas, security lighting, building facades, landscaping, schools, and general area illumination. With strong lumen performance, robust construction, and globally recognized certifications, the FLE Pro™ Series delivers long-term value for commercial and institutional lighting projects.



### Dimensions (mm)



Model	L	W	H	Model	L	W	H
10w	82	67	25	70w	200	152	26
20w	96	80	25	100w	270	185	27
30w	128	98	25	150w	330	220	27
50w	164	128	25	200w	370	260	28
				300w/400w	450	330	31

### Ordering information

Item	Watts	Lumens	CCT	Housing	CCT	Housing
AL675120	10w	1000	6500	Black	<b>Blank</b>	<b>Blank</b> Black
AL675121	20w	2000	6500	Black	<b>5</b>	<b>W</b> White
AL675122	30w	3000	6500	Black	<b>4</b>	
AL675123	50w	5000	6500	Black	<b>3</b>	
AL675124	70w	7000	6500	Black		
AL675125	100w	10000	6500	Black		
AL675126	150w	15000	6500	Black		
AL675127	200w	20000	6500	Black		
AL675128	300w	30000	6500	Black		
AL675129	400w	40000	6500	Black		

### Notes

- Lumen & Power tolerance up to 10%
- Cable spec: 0.2m\*0.75mm<sup>2</sup>
- Tempered Glass Thickness: 10w-30w = 3 mm, 50w-100w = 3.5 mm, 150w-400w = 4mm
- Die Cast Aluminum Housing Thickness: 10w-20w = 0.6 mm, 30w-70w = 0.7 mm, 100w-200w = 0.8 mm, 300w-400w = 1.3mm
- 4K/5K/65K = 100 lxw, 3K = 90 lxw
- Surge Protection: L-N 2KV; L, N-FG 2KV
- Recommended use: 12 hours / day to prevent product damage or voided warranty
- LED Chips: BMTc
- Cable length: 20 cm


### Packing information

Model	Pieces per master	Carton Dimensions (cm)	CBM per master	Gross Weight (KG)
10w	90	33.5 x 12 x 27.5	0.0110	14.4
20w	80	40 x 32 x 25	0.0320	15.5
30w	60	35 x 32 x 31	0.0347	16.5
50w	40	39 x 32 x 29	0.0361	17.1
70w	20	45 x 32 x 18	0.0259	16.5
100w	10	34 x 31 x 21	0.0221	10.6
150w	10	37.5 x 34 x 24.5	0.0312	14.8
200w	10	41 x 35 x 28	0.0401	18.6
300w / 400w	4	50 x 16 x 36.5	0.0292	14

## FLE™ Series

Economic Series

10w/20w/30w/50w/70w  
100w/150w/200w/300w/400w



Americanlite® FLE™ Series floodlights are economical, general-purpose LED luminaires designed to provide reliable illumination and cost-effective performance across a wide range of area-lighting applications. Utilizing proven LED technology, the FLE™ Series delivers luminous efficacy of up to 80 lumens per watt, offering a practical balance between light output, energy efficiency, and upfront cost. The series is optimized for projects where budget considerations are a primary driver while maintaining dependable performance and verified compliance.


The luminaire features a compact, modern design with a lightweight yet durable die-cast aluminum housing. The housing incorporates an efficient heat-sink design to support thermal stability and maintain LED operation within rated temperature limits across specified ambient conditions. This ensures consistent performance and dependable service life. Corrosion-resistant construction makes the fixture suitable for both indoor and outdoor environments.

A tempered glass lens provides increased strength compared to standard glass and improves safety by reducing the risk of sharp fragments in the event of breakage. The FLE™ Series operates on a universal input voltage range of 100–277V, 50/60Hz, allowing flexibility across a wide range of electrical systems.

The luminaire complies with CE, RoHS, and IEC standards, confirming adherence to recognized international requirements for safety, performance, and environmental responsibility. This level of certification supports confidence in the product's quality and reliability, even in cost-sensitive applications.

Designed for multiple mounting configurations, including wall, pole, and ground mounting, the Americanlite® FLE™ Series is suitable for applications such as parking areas, security lighting, building facades, landscaping, schools, and general indoor or outdoor area illumination. With durable construction, verified certifications, and an economical price point, the FLE™ Series provides a dependable lighting solution for projects focused on value and cost efficiency.

### Dimensions (mm)



Model	L	W	H	Model	L	W	H
10w	82	67	25	70w	200	152	26
20w	96	80	25	100w	270	185	27
30w	128	98	25	150w	330	220	27
50w	164	128	25	200w	370	260	28
				300w/400w	450	330	31

### Ordering information

Item	Watts	Lumens	CCT	Housing	CCT	Housing
AL675110	10w	800	6500	Black	<b>Blank</b> 6500K	<b>Blank</b> Black
AL675111	20w	1600	6500	Black	<b>5</b> 5000K	<b>W</b> White
AL675112	30w	2400	6500	Black	<b>4</b> 4000K	
AL675113	50w	4000	6500	Black	<b>3</b> 3000K	
AL675114	70w	5600	6500	Black		
AL675115	100w	8000	6500	Black		
AL675116	150w	12000	6500	Black		
AL675117	200w	16000	6500	Black		
AL675118	300w	24000	6500	Black		
AL675119	400w	32000	6500	Black		

### Notes

- Lumen & Power tolerance up to 10%
- 4K/5K/65K = 80 lxw
- 3K = 74 lxw
- LED Chips: BMTC
- Cable spec: 0.2m\*0.75mm<sup>2</sup>
- Cable length: 20 cm
- Surge Protection: L-N 2KV; L, N-FG 2KV
- Tempered Glass Thickness: 10w-30w = 3 mm, 50w-100w = 3.5 mm, 150w-400w = 4mm
- Die Cast Aluminum Housing Thickness: 10w-20w = 0.6 mm, 30w-70w = 0.7 mm, 100w-200w = 0.8 mm, 300w-400w = 1.3mm
- Recommended use: 12 hours / day to prevent product damage or voided warranty

### Packing information

Model	Pieces per master	Carton Dimensions (cm)	CBM per master	Gross Weight (KG)
10w	90	33.5 x 12 x 27.5	0.0110	14.4
20w	80	40 x 32 x 25	0.0320	15.5
30w	60	35 x 32 x 31	0.0347	16.5
50w	40	39 x 32 x 29	0.0361	17.1
70w	20	45 x 32 x 18	0.0259	16.5
100w	10	34 x 31 x 21	0.0221	10.6
150w	10	37.5 x 34 x 24.5	0.0312	14.8
200w	10	41 x 35 x 28	0.0401	18.6
300w / 400w	4	50 x 16 x 36.5	0.0292	14

## EX Pro™ Series

10w/20w/30w /50w  
100w/150w/200w/300w/400w



<b>IP65</b> 	<b>IK06</b> 	<b>Lumens</b> 120 L/W
<b>CRI</b> 80	<b>110°</b> Beam Angle	<b>VOLTS</b> 100-277
<b>PF</b> 0.90	<b>1.5KV</b> Surge Protection	<b>CCT</b> 3K-65K
<b>-20°C-40°C</b> 	<b>30,000</b> 	<b>3 YEARS</b> Warranty

Americanlite® LED Floodlight™ EX Pro™ Series, a multipurpose, highly efficient, energy saving replacements for HID & halogen fixtures. With a compact and modern design, the latest SMD LED technology, offers high brightness and a high lumen maintenance factor. We have developed an outstanding combination of high performance & bright LED's to create one of the most efficient fixtures with up to 120 lxw.

Versatile, light and strong housing made of die-cast aluminum, featuring high heat dissipation and superior aesthetics. Corrosion resistant with longer lifetime. Tempered glass, much stronger than regular glass, reduces the risk of injury caused by jagged glass shards. Advanced heat sink design ensures LED does not exceed temperature ratings across all specified ambient conditions. Universal voltage capacity 100-277V 50/60Hz.

Ideal for indoor and outdoor area lighting such as parking, security, landscaping, facades, schools, and many more. Works well for wall mounting, pole or ground mounting.

### Dimensions (mm)

Model	L	W	H	Model	L	W	H
10w	82	76	22	80w/100w	240	203	30
20w	116	103	22	150w	285	240	30
30w	134	115	25	200w	315	282	34
50w	196	160	27	300w	400	322	55
				400w	500	360	62

### Ordering information

Item	Watts	Lumens	CCT	Housing	CCT	Housing	Cable Length
AL675080	10w	1200	6500	Black	<b>Blank</b> 6500K	<b>W</b> White housing	<b>Blank</b> 10w-30w = .12m
AL675081	20w	2400	6500	Black	<b>5</b> 5000K		50w-200w = .15m
AL675082	30w	3600	6500	Black	<b>4</b> 4000K		300w/400w = .20m
AL675083	50w	6000	6500	Black	<b>3</b> 3000K		<b>1M</b> 1m
AL675084	80w	9600	6500	Black			
AL675085	100w	12000	6500	Black			
AL675086	150w	18000	6500	Black			
AL675087	200w	24000	6500	Black			
AL675088	300w	36000	6500	Black			
AL675089	400w	48000	6500	Black			

### Notes

- Lumen & Power tolerance ±10%
- PF: 10w/20w/30w = 0.50
- Surge Protection: 10w/20w = 1KV  
30w-400w = 1.5Kv
- Cable spec: 10w-100w = 3x0.52 mm2  
150w-400w = 3x0.75 mm2
- Cable length:  
10w-30w = .12m  
50w-200w = .15m  
300w/400w = .20m
- Glass Thickness: Tolerance ± 0.3mm  
10w = 2.5-2.7mm  
20w/30w = 3.0-3.2mm  
50w-400w = 3.3-3.5mm
- Recommended use: 12 hours / day  
to prevent product damage or voided warranty

### Packing information

Model	CBM (Master)	Pieces per master	Master Carton Dimensions (cm)
10w	0.0131	50	46.5 x 14.5 x 19.5
20w	0.0248	50	61.5 x 16.5 x 24.5
30w	0.0216	30	43 x 19 x 26.5
50w	0.0249	20	42 x 35 x 17
80w/100w	0.0310	12	52 x 26 x 23
150w	0.0288	10	35 x 30 x 27.5
200w	0.0342	8	34 x 33 x 30.5
300w	0.0449	4	45 x 27 x 37
400w	0.0351	2	54 x 16.5 x 39.5



## EX™ Series

10w/20w/30w /50w/80w  
100w/150w/200w/300w/400w



<b>IP65</b> 	<b>IK06</b> 	<b>Lumens</b> 100 L/W
<b>CRI</b> 80	<b>110°</b> Beam Angle	<b>VOLTS</b> 100-277
<b>PF</b> 0.90	<b>1.5KV</b> Surge Protection	<b>CCT</b> 6500K
 -20°C-40°C	 30,000	<b>3</b> YEARS Warranty

Americanlite® LED Floodlite™ EX™ Series, a multipurpose, highly efficient, energy saving replacements for HID & halogen fixtures. With a compact and modern design, the latest SMD LED technology, offers high brightness and a high lumen maintenance factor. We have developed an outstanding combination of high performance & bright LED's to create one of the most efficient fixtures with up to 100 lxw.

Versatile, light and strong housing made of die-cast aluminum, featuring high heat dissipation and superior aesthetics. Corrosion resistant with longer lifetime. Tempered glass, much stronger than regular glass, reduces the risk of injury caused by jagged glass shards. Advanced heat sink design ensures LED does not exceed temperature ratings across all specified ambient conditions. Universal voltage capacity 100-277V 50/60Hz.

Ideal for indoor and outdoor area lighting such as parking, security, landscaping, facades, schools, and many more. Works well for wall mounting, pole or ground mounting.

### Dimensions (mm)

Model	L	W	H	Model	L	W	H
10w	72	66	22	100w	242	203	26.5
20w	102	86	22	150w	282	242	26.5
30w	134	115	25	200w	315	280	27
50w	196	160	27	300w	378	338	32
80w	225	192	28	400w	440	388	45

### Ordering information

Item	Watts	Lumens	CCT	Housing	Housing	Cable Length
AL675070	10w	1000	6500	Black	W White housing	<b>Blank</b> 10w-30w = .12m 50w-200w = .15m 300w/400w = .20m
AL675071	20w	2000	6500	Black		
AL675072	30w	3000	6500	Black		<b>1M</b> 1m
AL675073	50w	5000	6500	Black		
AL675077	80w	8000	6500	Black		
AL675074	100w	10000	6500	Black		
AL675075	150w	15000	6500	Black		
AL675076	200w	20000	6500	Black		
AL675078	300w	30000	6500	Black		
AL675079	400w	40000	6500	Black		

### Notes

- Lumen & Power tolerance ±10%
- PF: 10w/20w/30w = 0.50
- Surge Protection: 10w/20w = 1KV  
30w-400w = 1.5Kv
- Cable spec: 10w-100w = 3x0.52 mm2  
150w-400w = 3x0.75 mm2
- Cable length:  
10w-30w = .12m  
50w-200w = .15m  
300w/400w = .20m
- Glass Thickness: Tolerance ± 0.3mm  
10w-30w = 2.5-2.7mm  
50w-200w = 3.0-3.2mm  
300w/400w = 3.0-3.2mm
- Recommended use: 12 hours / day  
to prevent product damage or voided warranty

### Packing information

Model	CBM (Master)	Pieces per master	Master Carton Dimensions (cm)
10w	0.0108	50	40 x 15.5 x 17.5
20w	0.0191	50	54 X 16.5 X 21.5
30w	0.0216	30	43 X 19 X 26.5
50w	0.0166	20	42 X 33 X 18
80w/100w	0.0209	8	52 X 17.5 X 23
150w	0.0148	5	30 X 18 X 27.5
200w	0.0216	5	33 X 21.5 X 30.5
300w	0.0336	5	39.5 x 23 x 37
400w	0.0449	4	45.5 x 23.5 x 42



## ES Series

10w/20w/30w/50w/80w  
100w/150w/200w/300w/400w



<b>IP65</b> Waterproof	<b>IK06</b> Impact resistant	<b>Lumens</b> 80 L/W
<b>CRI</b> >80	<b>110°</b> Beam Angle	<b>VOLTS</b> 100-265
<b>PF</b> >0.50	<b>1KV</b> Surge Protection	<b>CCT</b> 6500K
<b>-20°C-40°C</b> Temperature range	<b>30,000</b> Hours	<b>3 YEARS</b> Warranty

Americanlite® LED Floodlight™ ES Series, a multipurpose, highly efficient, energy saving replacements for HID & halogen fixtures. With a compact and modern design, the latest SMD LED technology, offers high brightness and a high lumen maintenance factor. We have developed an outstanding combination of high performance & bright LED's to create one of the most efficient fixtures.

Versatile, light and strong housing made of die-cast aluminum, featuring high heat dissipation and superior aesthetics. Corrosion resistant with longer lifetime. Tempered glass, much stronger than regular glass, reduces the risk of injury caused by jagged glass shards. Advanced heat sink design ensures LED does not exceed temperature ratings across all specified ambient conditions. Universal voltage capacity 100-265V 50/60Hz.

Ideal for indoor and outdoor area lighting such as parking, security, landscaping, facades, schools, and many more. Works well for wall mounting, pole or ground mounting.

### Dimensions (mm)

Model	L	W	H	Model	L	W	H
10w	72	66	22	100w	240	203	30
20w	102	86	22	150w	282	242	26.5
30w	116	103	22	200w	315	280	27
50w	160	134	25	300w	378	336	32
80w	196	160	27	400w	440	388	45

### Ordering information

Item	Watts	Lumens	CCT	Housing	CCT	Housing	Cable Length
AL675060	10w	800	6500	Black	<b>Blank</b> 6500K <b>3</b> 3000K	<b>W</b> White housing	<b>Blank</b> 10w-30w = .12m 50w-200w = .15m 300w/400w = .20m <b>1M</b> 1m
AL675061	20w	1600	6500	Black			
AL675062	30w	2400	6500	Black			
AL675063	50w	4000	6500	Black			
AL675064	80w	6400	6500	Black			
AL675065	100w	8000	6500	Black			
AL675066	150w	12000	6500	Black			
AL675067	200w	16000	6500	Black			
AL675068	300w	24000	6500	Black			
AL675069	400w	32000	6500	Black			



### Notes

- Lumen & Power tolerance ±10%
- Cable spec: 10w-100w = 3x0.52 mm2  
150w-400w = 3x0.75 mm2
- Cable length:  
10w-30w = .12m  
50w-200w = .15m  
300w/400w = .20m
- Glass Thickness: Tolerance ± 0.3mm  
10w-50w = 2.5-2.7mm  
80w-400w = 3.0-3.2mm
- Recommended use: 12 hours / day to prevent product damage or voided warranty

### Packing information


Model	CBM (Master)	Pieces per master	Master Carton Dimensions (cm)
10w	0.0118	50	41 x 16.5 x 17.5
20w	0.019	50	54.5 x 17 x 21.5
30w	0.0141	30	38 x 15.5 x 24
50w	0.0195	20	35.5 x 34.5 x 16
80w	0.0280	12	49 x 26 x 22
100w	0.0224	12	47.5 x 22 x 21.5
150w	0.0319	10	39.5 x 30 x 27
200w	0.0347	8	34 x 33.5 x 30.5
300w	0.0335	5	40 x 23 x 36.5
400w	0.0347	4	44.5 x 40 x 19.5



## E Series RGB

with Remote Control

10w/20w/30w/50w  
100w/150w/200w



Americanlite® LED Floodlight™ E Series RGB can be controlled remotely with an included remote. Create custom lighting effects with remote control : Adjust brightness, color, fade in/out, and flash rate. Can be controlled up to 6m.

Our unique technology DOB, includes built in memory chips which store the last lighting settings used even after turning it OFF or when disconnecting it from the power source. This allows users to set the color tones and effects desired and not worry about power outages, lighting relocation or having photocells control the hours of operation by having to reset the settings each time.

24-Key remote control functions

Brightness+ (7 steps)	Brightness- (7 steps)	Off	On
Static Red	Static Green	Static Blue	Static White
Static Orange	Static Pea Green	Static Dark Orchid	7 Color Flash
Static Dark Yellow	Static Cyan	Static Magenta	All Fade Out/In
Static Yellow	Static Light Blue	Static Pink	7 Color Fade
Static Yellow Light	Static Sky Blue	Static Purple	3 Color Transition

### Dimensions (mm)

Model	L	H	W	Model	L	H	W
10w	110	76	29	100w	255	175	30
20w	110	76	29	150w	320	230	32
30w	140	101	30	200w	336	242	32
50w	195	142	30				

### Ordering information

Item	Watts	Housing	Item	Watts	Housing
AL575250	10w	Black	AL575254	100w	Black
AL575251	20w	Black	AL575256	150w	Black
AL575252	30w	Black	AL575257	200w	Black
AL575253	50w	Black			

### Notes

- Surge Protection: 10w =1KV, 20w/30w = 1.5KV, 50w-200w=2.5KV
- Cable spec: 10w-30w = 0.5cm<sup>2</sup> PVC wire, 50w-200w = 0.75cm<sup>2</sup> PVC wire
- Battery: Lithium battery-3V 150mAH-CR2025 included in remote control
- Recommended use: 10-12 hours / day To avoid product damage or voided warranty

### Packing information

Model	CBM (Master)	Pieces per master	Master Carton Dimensions (cm)
10w	0.0317	60	36 x 28 x 31.5
20w	0.0317	60	36 x 28 x 31.5
30w	0.0335	40	38 x 34 x 26
50w	0.0308	20	38 x 23.5 x 34.5
100w	0.0470	20	37 x 31 x 41
150w	0.0349	10	36 x 36 x 27
200w	0.0435	10	42 x 37 x 28



## Warranty

---

Americanlite® is pleased to provide up to a 3 year limited warranty covering the LED fixtures on this catalogue. Americanlite® warrants that the LED fixtures comply with Americanlite®'s published specifications and are free from defects in materials and workmanship.

All our equipment is CE, ETL or UL approved and manufactured with approved components. Americanlite® reserves the right to change or improve the design or components of any of its products due to parts availability or changes in standards, without assuming any obligation to modify any product previously manufactured and without notice. All equipment is tested and inspected before shipment.

This warranty is void if the product is operated outside of its normal operating conditions. The foregoing warranty does not apply to failures caused by acts of God or as a result of any abuse, misuse, abnormal use, or use in violation of any applicable standard, code or instructions for use in installations, including, but not limited to, those contained in the Standards for the International Electrotechnical Commission. Americanlite® reserves and has the right to examine failed fixtures to determine the cause of failure, excessive lumen depreciation and patterns of usage.